

# THE BEST & LAST ROOF COATING YOU'LL EVER USE!



## GACOROOF IS IDEAL FOR:

- Aged Asphalt\*
- Aged EPDM and TPO/CPA†
- Built-Up
- Cap Sheet
- Composite
- Concrete
- Fiberglass
- Metal
- Modified Bitumen
- Torchdown
- Sprayed Polyurethane Foam
- Most Existing Coatings
- Low-Pitched Roofs
- Flat Roofs
- Mobile Homes
- RVs & Campers

\*Not for use on 3-tab asphalt or architectural shingles.

†May require GacoFlex E5320 2-Part Epoxy Primer/Filler. Verify adhesion with a GacoRoof Adhesion Test Kit.

WHITE  
GR1600

GRAY  
GR1628

GREEN  
GR1626

LIGHT TAN  
GR1670

RUSTIC  
GR1671

MEDIUM  
BLUE  
GR1672

BLACK  
GR1673

BROWN  
GR1674

RED  
GR1675

Note: Colors shown are printed representations of product color. Actual color may vary slightly due to surface texture, application technique and lighting conditions.

## FLIP OVER TO COMPARE FOR YOURSELF...

GACOROOF.COM 866 422 6489

**GacoFlex**<sup>®</sup>  
by Gaco Western<sup>®</sup>

# COMPARE FOR YOURSELF



	<b>GacoRoof</b>	Brand X
Warranty	<b>Limited 50-Year</b>	5-10 Years
Can Be Applied Between 32°F and 120°F	<b>YES</b>	NO
Withstands Permanent Ponding Water	<b>YES</b>	NO
Primer/Basecoat Required?	<b>NO*</b>	YES
Recoating Required?	<b>NO</b>	YES

- 2 coat application of same product  
Brand X requires multiple products
- Withstands permanent ponding water  
Brand X is 48 hours only
- Temperature application range 32°-120°F  
Brand X is 50°-90° F
- 1-12 hour cure time, dry to the touch  
Brand X is 24-48 hours
- 1 gallon = 100 sq. ft. per coat  
Brand X is 1.5 gallons
- Can be used on flat roofs  
Brand X requires 1/4" slope
- Can be rained on after 2 hours  
Brand X requires no rain, dew or fog within 24-48 hours
- Permanently flexible  
Brand X becomes brittle and begins to degrade over time
- Recoat can be done after cure time  
Brand X may require 24 hours before recoat
- Silicone Roof Coating  
Brand X sells all acrylic roof coatings
- Ponding waterproof  
Brand X is ponding water resistant
- 50 year warranty  
Brand X 5-10 year warranty
- No polyester mat between coats  
Brand X requires polyester mat
- UV resistant  
Brand X loses mil thickness due to UV exposure
- 22 mil system  
Brand X is 48-60 mil

\*Certain applications may require GacoFlex E5320 2-Part Epoxy Primer/Filler. Verify adhesion with a GacoRoof AdhesionTestKit.

GACOROOF.COM 866 422 6489

**GacoFlex**<sup>®</sup>  
by Gaco Western<sup>®</sup>